

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 1

-----

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES  
7405 PRODUCTION DRIVE  
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253  
Information phone/Fax: (440) 255-8900 / (440) 974-8358  
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)  
(800) 424-9300  
in Canada CANUTEC 613-996-6666

Product Class ADHESIVE  
Trade Name  
Product Code see above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
ACETONE	67-64-1	10 - 15	Y
Methyl Acetate	0079-20-9	< 5.0	Y
HEPTANE	142-82-5	< 5.0	Y
PETROLEUM NAPHTHA	64742-89-8	< 5.0	Y
MINERAL SPIRITS	8052-41-3	< 2.0	Y

Ingredient Notes:  
Remaining ingredients are not considered OSHA hazardous.

-----

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag mastic  
Appearance/Color: Tan  
Odor: Sharp  
Solubility (in water): insol. in water  
pH Value, +/- .3: Not Applicable  
Boiling Range: 150.°F - 250.°F (65.56°C - 121.11°C)  
Vapor Pressure (mmHg): 155.@ 68.°F (20.°C)

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 2

-----  
Evaporation Rate: 5.5 times Faster than n-Butyl Acetate  
  
Vapor Density: Heavier than air  
  
% Volatile, Weight 26.%  
% Volatile, Volume 40.%  
Specific Gravity: 1.29502  
VOC (less H2O or exempt) < 199 gr/L, 12%

**NOTE:**

\*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

-----  
**SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)**

Flammability Class I B  
Flash Range: 0.°F - 105.°F (-17.78°C - 40.56°C)  
Tag Closed Cup  
Explosive Range (LEL/UEL): 1.%  
6.5%

**EXTINGUISHING MEDIA:**

Carbon Dioxide---Dry Chemical---Foam  
Use water fog to cool material in vicinity of fire.

**SPECIAL FIRE-FIGHTING PROCEDURES:**

Use self-contained breathing apparatus with full facepiece  
operated in pressure demand with full protective equipment.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Any closed container may rupture when exposed to extreme heat.  
Solvent vapors are heavier than air and travel along the ground.  
Vapors given off are flammable and may be ignited in air explosively.

-----  
**SECTION V - HEALTH HAZARD DATA**

**ROUTES OF ENTRY:**

ENTRY THROUGH... Inhalation and skin most likely

**CARCINOGENICITY...**

NTP? N/E | IARC Monographs? N/E | OSHA? NO

**EFFECTS OF OVEREXPOSURE**

Eyes: Can cause irritation, redness, tearing and blurred vision.  
Skin: Prolonged or repeated contact can cause moderate  
irritation, defatting, and dermatitis.  
Inhalation: May cause nose or throat irritation. High concen-  
trations may cause acute central nervous system depression  
characterized by headaches, dizziness, nausea and confusion.  
Ingestion: Can cause gastrointestinal irritation, nausea,  
vomiting and diarrhea.

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 3

**FIRST AID MEASURES**

Eyes: Flush eyes gently with water for at least 15 minutes  
lifting eyelids occasionally; get prompt medical attention  
Skin: Wash thoroughly with soap and water; apply a mild skin cream.  
Remove contaminated clothing.  
Inhalation: Move affected person to fresh air; if breathing is  
difficult, administer oxygen; if breathing has stopped,  
give artificial respiration. Get medical attention.  
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

**CHRONIC HAZARDS**

NOTICE: Reports have associated repeated and prolonged  
occupational overexposure to solvents with permanent brain,  
nervous system, liver or kidney damage or may cause cardiac  
arrhythmia. INTENTIONAL misuse of this product by  
deliberately inhaling its vapors may be harmful or fatal.

**SECTION VI - STABILITY AND REACTIVITY**

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

**INCOMPATIBILITY:**

Keep away from strong oxidizing agents.

**CONDITIONS TO AVOID:**

Keep away from heat, spark, open flames and any ignition source.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Will produce fumes and smoke containing carbon monoxide and  
dioxide under fire conditions.

**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:**

**STEPS TO BE TAKEN IN CASE OF SPILL:**

Eliminate all ignition sources. Ventilate confined areas.  
(Open windows and doors). Wear appropriate protective clothing.  
Cover with absorbent. Scoop into sealable safety container.

**WASTE DISPOSAL METHOD:**

Dispose of following local, state, and federal regulations.

**SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Occupational Exposure Limits**

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ACETONE	750.00 PPM	N/est	1000.00 PPM	1000.00 PPM	750.00 PPM

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 4

---

Methyl Acetate	200.00 PPM	N/est	250.00 PPM	250.00 PPM	200.00 PPM
HEPTANE	400.00 PPM	N/est	N/est	500.00 PPM	400.00 PPM
PETROLEUM NAPHTHA	300.00 PPM	N/est	N/est	400.00 PPM	300.00 PPM
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM

**RESPIRATORY PROTECTION:**

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

**VENTILATION:**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

**PROTECTIVE CLOTHING:**

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

**EYE PROTECTION:**

Chemical goggles or safety glasses should be worn.

**HANDLING AND STORAGE PRECAUTIONS:**

Keep away from heat, spark and flame.  
Keep out of reach of children.  
Keep container closed while not in use.  
Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.  
Use only in a well ventilated area.

---

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

---

**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)**

**GROUND TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e.10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D  
Shipping Document: CONSUMER COMMODITY, ORM-D  
ERG Code: 171

---

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 5

-----

Units GREATER than 5L i.e. 5 gal. pail  
Proper Shipping Name: ADHESIVE  
Classification: CLASS 3  
DOT Label Required: Flammable Liquid, UN1133, Class 3  
Shipping Document: ADHESIVE,3,UN1133, PGIIII,  
for 50 gal. drum use PG II  
ERG Code: 128

**AIR TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D-AIR  
Shipping Document: Consumer Commodity, ORM-D  
ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
DOT Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III,  
for 50 gal. drum use PG II  
ERG Code: 128

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: class 9  
Label Required: ID8000  
Shipping Document: Consumer Commodity,9, ID8000  
ERG Code: 9L

Units GREATER than 5L i.e. 5 Gal. pail, 50 gal.drum  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PGIIII,  
for 50 gal. drum use PG II  
ERG Code: 3L

**MARINE - OCEAN TRANSPORT ( IMDG )**

Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1 gal.

Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: PL 200(R) Low VOC CONSTRUCTION ADHESIVE  
MSDS Number: P71200125-V  
Version Number 1  
Revision Date: OCT-13-2005  
Page Number: 6

-----  
(on Ocean container only, not required on cartons)  
Shipping Document: ADHESIVE, 3, UN1133, PG III, LTD.QTY.  
EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5 gal. pail, 50 gal drum  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PGIII,  
for 50 gal. drum use PG II  
EMS Code: F-E, S-D

-----  
**SECTION X - REGULATORY INFORMATION:**

The following ingredients are registered for TSCA 12B

Ingredient Name	CAS Number	Percent
ACETONE	67-64-1	11.14

SARA Section 311/312 Hazard Categories met: Fire Hazard,  
Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.